



TENERIO

Datasheet

TENERIO TR-25

Perfect Door Phone choice for the daily life

Phone Features	Administration Features	IP-PBX Features
<ul style="list-style-type: none"> • Video Resolution: 320 * 240, with 20pics per second. • Wide Angle Lens and IR LEDs for Night Vision Crystal Sound Quality. • Remote Door Opening. • Integrated Microphone and Speaker. • Water-proof Outdoor Unit: IP55. • Support all the VoIP Phones. 	<ul style="list-style-type: none"> • Auto Provisioning Using FTP/TFTP/HTTP/HTTPS/PnP. • Dial through IP PBX Using Phone Number. • Dial through IP PBX Using URL Address. • Conguration Managements with Web, Keypad on the Phone, and Auto Provisioning. 	<ul style="list-style-type: none"> • Video Codec: H.264. • Audio Codec: PCMU. • VAD, CNG , Echo Canceller.
Physical Features	Security Features	Network Features
<ul style="list-style-type: none"> • Camera: 2.0 Mega Pixels. • White Balance: Auto. • Lens: 4.0mm/F2.8. • Viewing Angle (Diagonal): 50. • Minimum Illumination: 1 LUX (without LED Illumination). • LED: 6 LEDs. • Power Requirement: DC12V. • Operating Temperature; -30 ~ 40°C Weight: 180g. • Size (WXHXD)185*68*50 mm. 	<ul style="list-style-type: none"> • Support HTTPS (SSL). • Support Login for Administration. • Sip Over TLS. 	<ul style="list-style-type: none"> • SIP v1(RFC2543), V2(RFC3261). Static IP/DHCP for IP Conguration. • 3 DTMF Modes: In-Band, RFC2833, SIP INFO. • HTTP/HTTPS Web Server for Management. • NTP for Auto Time Setting. • TFTP/FTP/HTTP/HTTPS Protocols.